



P.O. Box 600  
 San Felipe, TX 77473  
 Customer Service 800-864-1742  
 FAX 888-273-6226

# Liquid Ferrous Chloride Product Data Sheet

Revision Date: 3/5/13

## Description

Penccco's Ferrous Chloride is a clear green aqueous solution of soluble ferrous iron, manufactured to strict specifications from high quality raw materials. Penccco's unique manufacturing process renders a superior Ferrous Chloride that is stable at concentrations up to 36%. Penccco's Ferrous Chloride has a low free acid content.

## Application

Ferrous Chloride is manufactured for both municipal and industrial water treatment. Ferrous Chloride is very cost effective and widely used for odor, corrosion, and H<sub>2</sub>S control in municipal waste water systems. Ferrous Chloride is also used for hexavalent chrome reduction, phosphorous removal, and as a flocculation aid. It is also effective at removing metals, especially arsenic and selenium.

## Typical Analysis

Concentration (%FeCl <sub>2</sub> ).....	22 – 36%
Concentration (%Fe <sup>+2</sup> ).....	10-15%
Specific Gravity.....	1.2 – 1.4
Free Acid.....	<0.5%
pH.....	<2.0
Appearance.....	Green/Hazel color
Freezing Point.....	<32°F

## Health and Safety

Ferrous Chloride can cause irritation and burns to the skin and eyes. Ensure that individuals handling Ferrous Chloride have been fully trained regarding the MSDS, along with PPE requirements and specific operational procedures. In the event of an emergency, call 24 hr. CHEMTREC: 800-424-9300.

## Certifications

Ferrous Chloride is ANSI/NSF Standard 60 certified for use in potable water treatment and also meets or exceeds all AWWA standards.

## Product Handling and Shipping

Ferrous Chloride is shipped in railcars, tank trucks, totes, and drums. Suitable materials of construction include fiberglass, PVC, polypropylene, polyethylene, and Teflon. It is not compatible with most metals. It can be used with diaphragm metering pumps, providing the materials of construction are compatible. No dilution or preparation necessary.

DOT Classification: Ferrous Chloride, Solution

Hazard Class: 8      DOT ID Number: UN 1760      Packing Group: II

RQ = 100 Lbs.

Penccco provides the information contained in each material safety data sheet ("MSDS"), technical data sheet ("TDS"), product information brochure and/or information contained herein (including data and statements) in good faith and makes no representations as to its comprehensiveness or accuracy as of the date of publication. The MSDSs, TDSs, and product information brochures are referred to collectively as the "Data Sheets". It is the responsibility of the user to obtain and use the most recent version of the Data Sheets. Each Data Sheet relates only to the specific product designated therein and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and information are beyond the control of Penccco, Penccco expressly disclaims any and all liability as to any consequential damages or results obtained or arising from any use of the products or the information contained in the Data Sheets. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE DATA SHEETS OR THE RELATED PRODUCTS.